



Indigo™ Series 300 Ice Cube Machine

Model: ID-0302A

J₁Y-0304A

☐ ID-0303W

☐ IY-0305W





Ice Machine Electric

115/60/1 standard. (208-230/60/1 and 230/50/1 also available.)

Minimum circuit ampacity:

Air-cooled: 10.8 Water-cooled: Maximum fuse size: 15 amps 1ph

Specifications

BTU Per Hour:

4,600 (average), 5,450 (peak)

Refrigerant:

R-404A CFC-free

Operating Limits:

- Ambient Temperature Range: 35° to 110°F (1.7° to 43.3°C) Water Temperature Range: 35° to 90°F (1.7° to 32.2°C)
- · Water Pressure Ice Maker Water In: Min. 20 psi (137.9 kPA) Max. 80 psi (551.1 kPA)

Designed for operators who know that ice is critical to their business, the Indigo™ Series ice machine's preventative diagnostics continually monitor itself for reliable ice production. Improvements in cleanability and programmability make your ice machine easy to own and less expensive to operate.

- Space-Saving Design Up to 310 lbs. (141 kgs.) daily ice production and only 30" (76.20 cm) wide.
- Intelligent Diagnostics provide 24 hour preventative maintenance and diagnostic feedback for trouble free operation.
- Acoustical Ice Sensing Probe for reliable operation in challenging water conditions.
- EasyRead Display communicates operating status, cleaning reminders, and asset information through a blue illuminated display.
- Programmable Ice Production by On/Off Time, Ice Volume or Bin Level (with accessory bin level control) further improves energy efficiency and savings.
- Easy to Clean Foodzone Hinged front door swings out for easy access. Removable water-trough, distribution tube, curtain, and sensing probes for fast and efficient cleaning. Select components made with AlphaSan® antimicrobial.
- **DuraTech™ Exterior** provides superior corrosion resistance. Stainless finish with innovative clear-coat resists fingerprints and dirt.
- Available LuminIce™ Growth Inhibitor mitigates the growth of bacteria and yeast within the foodzone.



Ice Shape



Half Dice (.95 x 2.86 x 2.22 cm)



Dice 7⁄8" x 7⁄8" x 7∕8" (2.22 x 2.22 x 2.22 cm)













COMPANY WITH QUALITY SYSTEM **CERTIFIED BY DNV** = ISO 9001:2008 =

2110 South 26th Street PO Box 1720 Manitowoc, WI 54221-1720 USA Tel: 1.920.682.0161 Fax: 1.920.683.7589 www.manitowocice.com







i-300 on B-170 24.50" (62.23 cm) Storage Bin Installation Note Water Cooled clearance: 16.50" (41.91 cm) Top/Sides: 8" (20.3 cm) Back: 5" (12.7 cm) **B** Air Cooled clearance: 19.00" (48.26 cm) Top/Sides: 16" (40.6 cm) Back: 5" (12.7 cm) ED 6.00" (15.24 c 29.50" (74.9 cm) 30.00" (76.20 cm) (A) Electrical Entrance 1/2" (1.27 cm) Auxillary Base Drain Socket (B) 3/8" (0.95 cm) F.P.T. Water Condenser Inlet (water-cooled units) (E) 3/8" (0.95 cm) F.P.T. Ice Making Water Inlet © 1/2" (1.27 cm) F.P.T. Water Condenser Outlet F) 1/2" (1.27 cm) F.P.T. Ice Making Water Drain

Space-Saving Designs



i-300



i-300

	B-170	B-400
Height	41.50" 105.41 cm	54.50" 138.43 cm
Width	30.00" 76.20 cm	30.00" 76.20 cm
Depth	29.50" 74.93 cm	34.00" 86.30 cm
Bin Storage	150 lbs. 68.04 kgs.	290 lbs. 131.50 kgs.

Height includes adjustable bin legs 6.00" to 8.00", (15.24 to 20.32 cm) set at 6.00" (15.24 cm).

Specifications

		lce	Ice Production 24 Hours		Power Usage kWh/100 lbs. @90°Air/70°F	Water Usage/ 100 lbs. 45.4 kgs. of Ice	ENERGY	
	Model	Shape	70°Air/ 50°F Water	90°Air/ 70°F Water	1 Ph	Potable Water	STAR*	
AIR-COOLED	ID-0302A	dice	310 lbs.	225 lbs.	7.48	20.0 gal	*	
			141 kgs.	102 kgs.		75.7 L		
	IY-0304A	half-dice	310 lbs.	235 lbs.	7.38	20.0 gal	*	
			141 kgs.	107 kgs.		75.7 L		
	ID 0303W	ID-0303W dice	300 lbs.	260 lbs.	5.69	20.0 gal	NA	
OLED	ID-0303W		136 kgs.	118 kgs.		75.7 L		
WATER-COOLED	IY-0305W half-dice	half-dice	300 lbs.	260 lbs.	5.69	20.0 gal	NA	
			136 kgs.	118 kgs.		75.7 L		
W				led Condenser Water Usage / 100 lbs. /45.4 kgs. Of Ice: 193 gal/731 L. er-cooled models are excluded from ENERGY STAR qualification.				

(G) 3/4" (1.91 cm) Bin Drain

Order ice storage bin separately.

Accessories

LuminIce™ Growth Inhibitor reduces yeast and bacteria growth for a

cleaner ice machine.



Bin Level Control Allows ice bin level to be automatically set. Built-in LED light illuminates bin.



Arctic Pure®
Water Filters
Reduces
sediment and
chlorine odors for

better tasting ice.



AuCS® schedules and performs routine ice machine cleaning automatically.



47676 ©2014 Manitowoc 2/14. Continuing product improvement may necessitate change of specifications without notice

2110 South 26th Street
PO Box 1720
Manitowoc, WI 54221-1720 USA

Tel: 1.920.682.0161 Fax: 1.920.683.7589 www.manitowocice.com

